

ÁNGULOS



Productos de fabricados en grado de acero estructural ASTM-A-36, se suministran en tramos de 6.10 mts.

ÁNGULOS DE LADOS IGUALES

MEDIDA ESTÁNDAR		PESO		ÁREA		
pulg	mm	kg/m	pza 6.1 m	cm ²		
1/8"	3/4"	3.18	19.05	0.88	5.368	1.11
	1"		25.4	1.19	7.259	1.52
	1 1/4"	31.75	1.5	9.15		1.93
	1 1/2"	38.1	1.83	11.163		2.34
	1 3/4"	44.45	2.14	13.054		2.74
	2"	50.8	2.46	15.006		3.1
3/16"	1"	4.76	25.4	1.73	10.553	2.21
	1 1/4"	31.75	2.2	13.42		2.79
	1 1/2"	38.1	2.68	16.348		3.43
	1 3/4"	44.45	3.15	19.215		4.03
	2"	50.8	3.63	22.143		4.61
	2 1/2"	63.5	4.61	28.121		5.81
	3"	76.2	5.52	33.672		7.03
	3 1/2"	88.9	6.55	39.955		8.36
1/4"	1"	6.35	25.4	2.22	13.542	2.8
	1/4"	31.75	2.86	17.446		3.72
	1 1/2"	38.1	3.48	21.228		4.4
	1 3/4"	44.45	4.12	25.132		5.2
	2"	50.8	4.75	28.975		6.06
	2 1/2"	63.5	6.1	37.21		7.68
	3"	76.2	7.29	44.469		9.29
	3 1/2"	88.9	8.63	52.643		10.9
	4"	101.6	9.82	59.902		12.52

MEDIDA ESTÁNDAR		PESO		ÁREA		
pulg	mm	kg/m	pza 6.1 m	cm ²		
5/16"	2"	7.94	50.8	5.83	35.563	7.42
	2 1/2"		63.5	7.44	45.384	9.48
	3"		76.2	9.08	55.388	11.48
	3 1/2"		88.9	10.71	65.331	13.48
	4"		101.6	12.2	74.42	15.48
	5"		127	15.47	94.367	19.723
3/8"	2"	9.52	50.8	6.99	42.639	8.77
	2 1/2"		63.5	8.78	53.558	11.16
	3"		76.2	10.72	65.392	13.61
	3 1/2"		88.9	12.65	77.165	16
	4"		101.6	14.58	88.938	18.45
	5"		127	18.3	111.63	23.29
	6"		152.4	22.17	135.237	28.13
1/2"	3"	12.7	76.2	13.99	85.339	17.74
	3 1/2"		88.9	16.52	100.772	20.97
	4"		101.6	19.05	116.205	24.19
	5"		127	24.11	147.071	30.65
	6"		152.4	29.17	177.937	37.1
5/8"	4"	15.88	101.6	23.36	142.496	35.1
	6"		152.4	36.01	219.661	45.87
3/4"	6"	19.05	152.4	42.71	260.531	54.45